

# IP protected platform scale KERN IXS



## Platform scale with stainless steel IP68 indicator, XL display and EC type approval [M]

### Features

- **Ideal for the robust industrial applications**
- **Robust stainless steel indicator** with IP68 protection, ideal for industrial applications, for easy and hygienic cleaning, with integrated power supply. Wall mount standard. For additional information see page 136, KERN KXS-TM
- **Superior display size:** digit height 55 mm. Bright backlight for easy reading of weighing results, even in poor lighting conditions
- **Stainless steel weighing plate**
- Substruction in wing design, extremely resistant to bending, steel, lacquered

- **3 Load cells** aluminium, silicone-coated. **IP65:** Dust and spray protected
- **ESD drain to protect against electrostatic discharge** e.g. for electrostatically-charged weighing objects or people who work with the scale
- Thanks to the RS-232, RS-485 and Bluetooth (optional) interfaces, the scale can easily be connected to existing networks to facilitate data exchange between scale, PC or printer

### Technical data

- Large backlit LCD display, digit height 55 mm
- Weighing plate dimensions, stainless steel, WxDxH
  - A** 300x240x86 mm
  - B** 400x300x89 mm
  - C** 500x400x123 mm
  - D** 650x500x133.5 mm
- Dimensions of display device WxDxH 232x170x80 mm
- Cable length of display device approx. 2,5 m
- Permissible ambient temperature -10 °C / 40 °C

### Accessories

- **Rechargeable battery pack internal**, operating time up to 80 h without backlight, charging time approx. 12 h, must be ordered at purchase, KERN GAB-A04
- **Bluetooth data interface** for wireless data transfer to PC or tablets, must be ordered at purchase, KERN KXS-A02
- **Data interface RS-232**, must be ordered at purchase, KERN KXS-A04
- **Data interface RS-485**, must be ordered at purchase, KERN KXS-A01
- **Foot switch**, must be ordered at purchase, for details see page 160, KERN KXS-A03
- **Suitable printers** see page 157 ff.

### STANDARD



### OPTION











































### FACTORY



Model	Weighing range [Max] kg	Readout [d] g	Verification value [e] g	Minimum load [Min] g	Net weight approx. kg	Weighing plate	Options			
							Verification		DAkkS Calibr. Certificate	
							M III KERN		DAkkS KERN	
Dual-range scale switches automatically to the next largest weighing range [Max] and readout [d].										
IXS 6K-3M	3   6	1   2	1   2	20   40	5,1	A		965-228		963-128
IXS 10K-3M	6   15	2   5	2   5	40   100	5,1	A		965-228		963-128
IXS 10K-3LM	6   15	2   5	2   5	40   100	10,15	B		965-228		963-128
IXS 30K-2M	15   30	5   10	5   10	100   200	10,15	B		965-228		963-128
IXS 30K-2LM	15   30	5   10	5   10	100   200	20,5	C		965-228		963-128
IXS 60K-2M	30   60	10   20	10   20	200   400	10,15	B		965-229		963-129
IXS 60K-2LM	30   60	10   20	10   20	200   400	20,5	C		965-229		963-129
IXS 100K-2M	60   150	20   50	20   50	400   1000	20,5	C		965-229		963-129
IXS 100K-2LM	60   150	20   50	20   50	400   1000	36	D		965-229		963-129
IXS 300K-2M	150   300	50   100	50   100	1000   2000	36	D		965-229		963-129

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

# KERN Pictograms

 <b>Internal adjusting:</b> Quick setting up of the balance's accuracy with internal adjusting weight (motordriven).	 <b>Recipe level A:</b> Separate memory for the weight of the tare container and the recipe ingredients (net total).	 <b>Suspended weighing:</b> Load support with hook on the underside of the balance.
 <b>Adjusting program CAL:</b> For quick setting up of the balance's accuracy. External adjusting weight required.	 <b>Recipe level B:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.	 <b>Battery operation:</b> Ready for battery operation. The battery type is specified for each device.
 <b>Memory:</b> Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 <b>Recipe level C:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display. Additional convenient functions, such as barcode and back calculation functions.	 <b>Rechargeable battery pack:</b> Rechargeable set.
 <b>Data interface RS-232:</b> To connect the balance to a printer, PC or network.	 <b>Totalising level A:</b> The weights of similar items can be added together and the total can be printed out.	 <b>Mains adapter:</b> 230V/50Hz in standard version for EU. On request GB, AUS or USA version available.
 <b>RS-485 data interface:</b> To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.	 <b>Totalising level C:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display. Additional convenient functions, such as barcode and back calculation.	 <b>Power supply:</b> Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
 <b>USB data interface:</b> To connect the balance to a printer, PC or other peripherals.	 <b>Strain gauges:</b> Electrical resistor on an elastic deforming body.	 <b>Tuning fork principle:</b> A resonating body is electromagnetically excited, causing it to oscillate.
 <b>Bluetooth data interface:</b> To transfer data from the balance to a printer, PC or other peripherals.	 <b>Percentage determination:</b> Determining the deviation in % from the target value (100 %).	 <b>Electromagnetic force compensation:</b> Coil inside a permanent magnet. For the most accurate weighings.
 <b>WLAN data interface:</b> To transfer data from the balance to a printer, PC or other peripherals.	 <b>Weighing units:</b> Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 <b>Single cell technology:</b> Advanced version of the force compensation principle with the highest level of precision.
 <b>Control outputs (optocoupler, digital I/O):</b> To connect relays, signal lamps, valves, etc.	 <b>Weighing with tolerance range:</b> Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning.	 <b>Verification possible:</b> The time required for verification is specified in the pictogram.
 <b>Interface for second balance:</b> For direct connection of a second balance.	 <b>Vibration-free weighing:</b> (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value.	 <b>DAkkS calibration possible:</b> The time required for DAkkS calibration is shown in days in the pictogram.
 <b>Network interface:</b> For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.	 <b>Protection against dust and water splashes IPxx:</b> The type of protection is shown in the pictogram. For details see the glossary.	 <b>Package shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram.
 <b>GLP/ISO log:</b> The balance displays the weight, date and time, regardless of a printer connection.	 <b>ATEX explosion protection:</b> Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device.	 <b>Pallet shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram.
 <b>GLP/ISO log:</b> With weight, date and time. Only with KERN printers, see "Accessories"	 <b>Stainless steel:</b> The balance is protected against corrosion.	 <b>Warranty:</b> The warranty period is shown in the pictogram.
 <b>Piece counting:</b> Reference quantities selectable. Display can be switched from piece to weight.		

## Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2000 kg. In combination with a DAkkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.

## Your KERN specialist dealer:

Thanks to the high level of automation, we can carry out DAkkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

### Range of services:

- DAkkS calibration of balances with a maximum load of up to 6 t
- DAkkS calibration of weights in the range of 1 mg - 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages D, GB, F, I, E, NL